

ATLANTIC



Caractéristiques

Technische Daten

Technical details

Mode de fabrication	Herstellungsart	Manufacturing method	Tufted
Aspect	Art des Flors	Pile type	Loop pile
Type de teinture	Art der Färbung	Dyeing method	Solution Dyed
Surface	Polmaterial	Pile content	100% Polyamide
Jauge	Teilung	Gauge	1/10
Dossier	Rücken	Backing	Action Backing
Poids du velours	Poleinsatzgewicht	Pile weight	ca. 1000 gr/m ²
Hauteur du velours	Polhöhe	Pile height	ca. 5,5 mm
Epaisseur totale	Gesamtdicke	Total Thickness	ca. 6,5 mm
Poids total	Gesamtgewicht	Total weight	ca. 2150 gr/m ²
Nombre de points	Polnoppenzahl	Tuft density	ca. 182 500/m ²
Largeur	Lieferbreite	Width	4 m
Classement feu	Brennverhalten	Flammability classification	Bfl S1 according to EN13501-1
Classement antistatique	Antistatisches Verhalten	Electrostatic properties	Walking Test < 2,0 KV Resistance $\geq 10^{10}$
Domaine d'usage	Einsatzbereich	Suitability	EN1307 - 33 - Commercial Heavy
Application fauteuil roulant	Stuhlrolleneignung	Castor chair suitability	Class A acc. to EN 985 - Intensive use
Isolation phonique	Trittschalldämmung	Sound absorption	26 dB - ISO 140-8
Solidité des coloris :	Farbechtheit :	Colour fastness :	
Lumière	Lichtechtheit	To light	≥ 7 according to ISO 105-B02
Frottement	Reibecktheit	To rubbing	≥ 4 according to ISO 105-X12
Resistance au chlor	Chlorechtheit	Bleach resistance	Yes

Maintenance

The fibre blend used has exceptional resistance to soiling and facilitates the use of recognised cleaning solutions.

This carpet must be sold and installed in accordance with BS5325. Chair mats are recommended for use under castor chairs.

All specifications are subject to normal commercial tolerances and subject to change where they improve the product's performance.

Pile reversal / shading

Carpets may be subject to permanent pile reversal, also known as "shading" or "watermarking". The pile in certain areas may become distorted, giving the appearance of areas of light and shade. No specific cause of this has been identified and it is no manufacturing fault.


We reserve the right to make technical alterations and improvements to this product. Colour variations from the original sample can occur.

DIBt - Allgemeine bauaufsichtliche Zulassung Nr. Z-156.601-1010

TÜV Emission testing - The results comply with the emission threshold of :

AgBB - Germany
Belgian VOC regulation
BREEAM Exemplary level
French VOC regulation
LEED V4 (outside North America)









16

Manufactured by :
TAPIBEL NV.
Industrielaan 4
B-3900 Overpelt
1611

DOP 000576A-001
EN 14041

EN 1307

ATLANTIC Action backing

For use as floor covering in
buildings (EN 14041) according to the
manufacturer's specifications